

## DUCTING

### DTPR/RFH

Excellent flexibility and lightweight. Extruded black thermoplastic rubber reinforced with a steel spiral. Resistant to high temperature, chemicals and abrasion. For suction and discharge of abrasive powders, fumes, shavings, vapours and for medium to heavy duty industrial abrasive applications. > Temperature range: -40°C to +120°C.



I.D. MM	I.D. INCH	BENDING RADIUS MM	VACUUM M/H2O	WEIGHT G/M	LENGTH MTR	PART No.
50	2"	40	2	210	10	DTPR2
57	2¼"	50	1.7	245	10	DTPR225
65	2½"	55	1.7	260	10	DTPR25
75	3"	65	1.7	390	10	DTPR3
90	3½"	75	1.6	450	10	DTPR35
100	4"	85	1.3	495	10	DTPR4
112	4½"	95	1.2	595	10	DTPR45
125	5"	105	1.0	690	10	DTPR5
150	6"	125	0.8	910	10	DTPR6
180	7"	150	0.5	1210	10	DTPR7
200	8"	165	0.4	1320	10	DTPR8
228	9"	185	0.4	1490	10	DTPR9
250	10"	210	0.4	1800	10	DTPR10
300	12"	250	0.3	2100	10	DTPR12
350	14"	300	0.3	2450	10	DTPR14
400	16"	350	0.3	2800	10	DTPR16