

MARINE EXHAUST HOSE

A lightweight suction and delivery hose incorporating a corrugated cover for extra flexibility. For the conveying of wet exhaust fumes in marine applications. > Tube: black smooth exhaust, gas and seawater resistant > Reinforcement: high tensile textile cord and steel wire helix > Cover: black corrugated > Temperature range: -30°C to +100°C > Lloyds approved. Meets or exceeds SAE 2006 R2.



PART No.	I.D. INCH	I.D. MM	O.D. MM	W.P. PSI	WEIGHT KG/MTR	COIL LENGTH MTR
MEX25	1"	25	33.5	43	0.48	20
MEX32	1¼"	32	40	43	0.60	20
MEX38	1½"	38	46	43	0.68	20
MEX45	1¾"	45	53	43	0.80	20
MEX51	2"	51	59	43	0.97	20
MEX57	2¼"	57	67	43	1.08	20
MEX60	2 3/8"	60	68	43	1.12	20
MEX63	2½"	63	72	43	1.18	20
MEX70	2¾"	70	78	43	1.30	20
MEX76	3"	76	85	43	1.34	20
MEX90	3½"	90	99	43	1.57	20
MEX102	4"	102	111	43	1.88	20
MEX114	4½"	114	126	43	2.25	20
MEX127	5"	127	137	43	2.35	20
MEX152	6"	152	163	43	2.95	20
MEX203	8"	203	213	43	4.50	20