

POWAFLEX AIRFLAT AIR HOSE

Powaflex Airflat is a lightweight, hardwearing, rugged layflat air hose with high tensile strength. Manufactured from a rubber/PVC blend, U.V. stabilised, extruded through a circular woven jacket made from high tenacity filament polyester yarn.

> Temperature range: -30°C to +75°C > Standard lengths: 20mtr, 30mtr, 60mtr and available up to 200mtrs - yellow cover



I.D. INCH	I.D. MM	PART No.	O.D. MM	W.P. PSI	WEIGHT KG/MTR	TENSILE STRENGTH KG
¾"	20	PAF20	24.6	300	0.210	1900
1"	25	PAF25	30.4	300	0.275	2300
1½"	38	PAF38	43.0	300	0.390	3500
2"	51	PAF51	56.8	300	0.650	7900
2½"	65	PAF65	70.8	250	0.750	6700
3"	76	PAF76	82.2	250	0.950	8100

POWAFLEX AIRFLAT COMPRESSED AIR HOSE ASSEMBLY

Powaflex Airflat, lightweight, hardwearing rubber layflat air hose with high tensile strength. UV stabilised. Complete with claw couplings and double bolt claw clamps. 20 metre assemblies.



PART No.	I.D. INCH	I.D. MM	O.D. MM	W.P. PSI
PAF2020F	¾	20	24.6	300
PAF2520F	1	25	30.4	300

Sizes available up to 3" in variable lengths - POA.