

POWAFLEX CONTRACTORS FLEXIBLE WATER SUCTION HOSE

Convuluted cover for improved flexibility. Suction and delivery of water and light to medium density slurries. > Tube: SBR/NR black
> Reinforcement: high tensile textile cord and steel wire helix > Cover: SBR/NR black > Temperature range: -35°C to +80°C



| PART No. | I.D. INCH | I.D. MM | O.D. MM | W.P. PSI | B.P. PSI | LENGTH MTR |
|----------|-----------|---------|---------|----------|----------|------------|
| PCWS76 | 3 | 76 | 87 | 50 | 150 | 6 |
| PCWS102 | 4 | 102 | 116 | 50 | 150 | 6, 20 |
| PCWS152 | 6 | 152 | 166 | 50 | 150 | 3, 6, 20 |
| PCWS203 | 8 | 203 | 224 | 50 | 150 | 3, 6, 20 |
| PCWS254 | 10 | 254 | 278 | 50 | 150 | 3 |
| PCWS305 | 12 | 305 | 333 | 50 | 150 | 3 |

POWAFLEX CONTRACTORS SUCTION PUMP HOSE ASSEMBLY

A quality, flexible rubber water suction hose assembly, complete with male and female Bauer couplings with lever closure ring and Band-It preformed clamps, fitted.



| PART No. | I.D. INCH | I.D. MM | O.D. MM | W.P. PSI | B.P. PSI | ASSEMBLY LENGTH MTR |
|-----------|-----------|---------|---------|----------|----------|---------------------|
| PCWS766F | 3 | 76 | 87 | 50 | 150 | 6 |
| PCWS1026F | 4 | 102 | 116 | 50 | 150 | 6 |
| PCWS1523F | 6 | 152 | 166 | 50 | 150 | 3 |
| PCWS2033F | 8 | 203 | 224 | 50 | 150 | 3 |
| PCWS2543F | 10 | 254 | 278 | 50 | 150 | 3 |
| PCWS3053F | 12 | 305 | 333 | 50 | 150 | 3 |