

PVC PRESSURE HOSE

POWAFLEX BLUE SUPA WASH HOSE

A premium quality washdown hose. Designed for rural and commercial washdown applications. PVC/Nitrile blend for extra flexibility, even at low temperatures. Metallic blue cover. Temperature range: 0°C to 60°C.



| PART No. | I.D. INCH | I.D. MM | O.D. MM | W.P. PSI | COIL LENGTH MTR |
|----------|-----------|---------|---------|----------|-----------------|
| PFBSW12 | 1/2 | 12.5 | 18.5 | 150 | 20, 60, 100 |
| PFBSW19 | 3/4 | 19.0 | 28.0 | 150 | 20, 60, 100 |
| PFBSW25 | 1 | 25.0 | 35.0 | 150 | 20, 60, 100 |
| PFBSW32 | 11/4 | 32.0 | 44.0 | 150 | 20, 60, 100 |
| PFBSW38 | 1½ | 38.0 | 51.0 | 150 | 20, 60, 100 |

POWAFLEX BLUE SUPA WASH HOSE ASSEMBLIES

Powaflex Supa Wash hose fitted with brass nut and tail and adjustable spray nozzle. $\frac{1}{2}$ " and $\frac{3}{4}$ " with crimped ends, 1" with nylon double bolt clamps.



| PART No. | I.D. INCH | I.D. MM | O.D. MM | W.P. PSI | FEMALE BSP SIZE INCH | COIL LENGTH MTR |
|------------|-----------|---------|---------|----------|----------------------|-----------------|
| PFBSW1220F | 1/2 | 12.5 | 18.5 | 150 | 1 | 20 |
| PFBSW1920F | 3/4 | 19.0 | 28.0 | 150 | 1 | 20 |
| PFBSW2520F | 1 | 25.0 | 35.0 | 150 | 1 | 20 |