

PUMPMAN - RUBBER LAYFLAT DISCHARGE HOSE

Heavy duty pump discharge hose for water, slurry, etc. Abrasive resistant rubber, U.V. resistant, flexible and strong for tough conditions. > Temperature range: -30°C to +70°C.



PART No.	I.D. INCH	I.D. MM	WALL THICKNESS MM	W.P. PSI	WEIGHT KG/MTR	LENGTH MTR
PM25	1	25	2.2	200	0.23	50
PM38	1½	38	2.2	200	0.30	67, 100, 200
PM50	2	51	2.3	200	0.50	20, 100
PM76	3	76	2.5	200	0.70	20, 30, 100
PM102	4	102	2.7	150	1.02	20, 100
PM150	6	152	2.9	150	1.75	20, 100
PM200	8	203	3.5	150	2.40	20, 100
PM250	10	253	3.5	135	2.97	20, 100
PM300	12	305	4.5	100	4.50	20, 50, 100

PUMPMAN RUBBER LAYFLAT PUMP HOSE ASSEMBLY

A quality rubber layflat discharge hose assembly, complete with male and female Bauer couplings with lever closure ring and Band-It preformed clamps, fitted.



PART No.	I.D. INCH	I.D. MM	WALL THICKNESS MM	W.P. PSI	ASSEMBLY LENGTH MTR
PM7625F	3	76	2.5	150	25
PM10220F	4	102	2.7	150	20
PM15020F	6	152	2.9	150	20
PM20020F	8	203	3.5	150	20
PM25020F	10	254	3.5	135	20
PM30020F	12	305	4.5	100	20