










AIP AIR HOSE COUPLINGS – QUICK CONNECT

STANDARD COUPLER - STEEL

|  | PART No. | HOSE SIZE |
|--|----------|-----------|
| | 20SH | 1/4" |
| | 30SH | 3/8" |
|  | PART No. | BSP SIZE |
| | 20SM | 1/4" |
| | 30SM | 3/8" |
|  | PART No. | BSP SIZE |
| | 20SF | 1/4" |
| | 30SF | 3/8" |
|  | PART No. | HOSE SIZE |
| | 20PH | 1/4" |
| | 30PH | 3/8" |
|  | PART No. | BSP SIZE |
| | 20PM | 1/4" |
| | 30PM | 3/8" |
|  | PART No. | BSP SIZE |
| | 20PF | 1/4" |
| | 30PF | 3/8" |

ONE TOUCH COUPLER - STEEL

|  | PART No. | HOSE SIZE |
|---|----------|-----------|
| | 20SHT | 1/4" |
| | 30SHT | 3/8" |
|  | PART No. | BSP SIZE |
| | 20SMT | 1/4" |
| | 30SMT | 3/8" |
|  | PART No. | BSP SIZE |
| | 20SFT | 1/4" |
| | 30SFT | 3/8" |

MULTI COUPLER

Complete with 1/4" male BSP couplings.

| | | |
|---|---|---|
|  SMV POA |  SMY POA |  SMM POA |
|---|---|---|

SPECIFICATION

| MATERIAL | STEEL |
|-------------------|-----------------------|
| WORKING PRESSURE | 15kgf/cm ² |
| MAXIMUM PRESSURE | 20kgf/cm ² |
| TEMPERATURE RANGE | -20°C TO +80°C |