

## PVC PRESSURE HOSE

### TRADEFLEX

Excellent flexibility at low temperature. A hose for the transfer of air, water and ideal for the tradesperson as an air compressor hose. Blue smooth outer cover with a black inner wall.

UV stabilised > Conforms to AS 2554 Class B > Temperature range: 0°C to 60°C > \* Supplied on wooden reels



PART No.	I.D. INCH	I.D. MM	O.D. MM	W.P. PSI	WEIGHT (KG/M)	COIL LENGTH MTR
TF6	¼	6.0	12.0	232	0.12	20, 100, 300*
TF8	5/16	8.0	14.0	232	0.14	20, 100, 300*
TF10	3/8	10.0	16.0	232	0.16	15, 20, 30, 100, 200*
TF12	½	12.5	19.0	232	0.21	20, 100, 200*

### TRADEFLEX FITTED ASSEMBLIES

Pre-assembled quality air hose and fittings in popular lengths, incorporating crimped-on quick connect quality AIP couplings in socket and plug configuration and ready for immediate service. AIP "one touch" quick connect couplings also available P.O.A.



PART No.	I.D. INCH	I.D. MM	W.P. PSI	COIL LENGTH MTR
TFA1010	3/8	10.0	232	10
TFA1015	3/8	10.0	232	15
TFA1020	3/8	10.0	232	20
TFA1030	3/8	10.0	232	30
TFA1210	½	12.5	232	10
TFA1215	½	12.5	232	15
TFA1220	½	12.5	232	20
TFA1230	½	12.5	232	30