

| I.D. INCH | PART No. | WALL THICKNESS MM | TENSILE STRENGTH KG | BURST PRESSURE MPa | WEIGHT KG/MTR | COIL LENGTH MTR |
|-----------|----------|-------------------|---------------------|--------------------|---------------|-----------------|
| 2" | TIH50 | 2.8 | 4,700KG | 6.5 | 0.50 | 200 |
| 2 ½" | TIH65 | 2.9 | 6,700KG | 5.5 | 0.70 | 200 |
| 3" | TIH76 | 3.1 | 8,100KG | 5.0 | 0.95 | 200 |
| 3 ½" | TIH90 | 3.2 | 9,100KG | 4.0 | 1.12 | 200 |
| 4" | TIH102 | 3.2 | 10,200KG | 4.0 | 1.32 | 200 |
| 4 ½" | TIH114 | 3.2 | 11,200KG | 3.5 | 1.43 | 200 |
| 5" | TIH127 | 3.3 | 12,200KG | 3.0 | 1.68 | 200 |
| 6" | TIH150 | 3.4 | 15,800KG | 3.0 | 1.90 | 200 |

Temperature range: -30°C to +75°C



Travelflex

- Highly abrasive resistant for tough Australian conditions
- Process of manufacture ensures an excellent adhesion between rubber and textile
- The nitrile rubber compound is highly resistant to oil and other chemicals
- Resilient and flexible rubber to resist kinking with excellent UV resistance
- Lightweight yet strong
- Pliable for flat storage
- Lower friction - high performance

TEN YEAR WARRANTY



NS-ISO 9001 SERTIFISERT BEDRIFT

