

# BUTTERFLY VALVE PLUS ACTUATORS

SIZE N.B.	TABLE E	NBR SEAT	WAFER C.I. BODY	316 S/S DISC	316 S/S STEM	VALVE COMPLETE WITH DOUBLE ACTING AIR ACTUATOR	VALVE COMPLETE WITH SINGLE ACTING/SPRING RETURN ACTUATOR
50	✓	✓	✓	✓	✓	BFVDA50	BFVSASR50
65	✓	✓	✓	✓	✓	BFVDA65	BFVSASR65
80	✓	✓	✓	✓	✓	BFVDA80	BFVSASR80
100	✓	✓	✓	✓	✓	BFVDA100	BFVSASR100
125	✓	✓	✓	✓	✓	BFVDA125	BFVSASR125
150	✓	✓	✓	✓	✓	BFVDA150	BFVSASR150
200	✓	✓	✓	✓	✓	BFVDA200	BFVSASR200
250	✓	✓	✓	✓	✓	BFVDA250	BFVSASR250
300	✓	✓	✓	✓	✓	BFVDA300	BFVSASR300

NITRILE Seat = Nitrile Butadiene, (Buna-N)  
 Max Temp = 100°C Min Temp = -18°C  
 Suitable for general applications, including sanitary and some hydrocarbon services.

*Other seat materials available on request.*



**AIR ACTUATORS**  
 Operating pressure – 6 bar.  
 for open/close control, refer to solenoid/pilot valves