

PU CONCRETE PLACEMENT HOSE

FOR DROP HOSE APPLICATIONS



Easy to handle yet sturdy cement discharge hose.

POWAFLEX PU/CPH

The development of this hose was initiated to answer a need in the North American market for an easy to handle concrete placement hose. The hose is an ideal answer for ICF forms as well as tall walls and columns where space is minimal. The lay flat design allows better flow control and lower placement rates when necessary. The hose conforms with or exceeds strict safety regulations such as the North American CPMA 27-2000.



Powaflex PU/CPH is made from extruded thermoplastic polyether based polyurethane (TPU) with excellent wear and tear characteristics. The circular woven reinforcement is made from an extra strong yarn. The "extrusion through the weave" production method gives a very strong bond between cover and lining and encapsulates the woven reinforcement. The heavily reinforced weave ensures minimum extension in length and minimum "snaking" or bending of the hose.



Benefits

- > Meets/exceeds CPMA requirements
- > 1/3 the weight
- > Operator friendly
- > More consistent flow at lower placement rates
- > Ease of pour in tight areas
- > Bright colour for visibility and safety
- > Superior resistance to weather and ageing
- > Cleans up easily

I.D.		PART No.	WALL THICKNESS	WEIGHT	W.P.		B.P.	
INCH	MM				PSI	BAR	PSI	BAR
4	111.0+2.0	PPUCPH4	4.2	1.75	1250	86	2500	172

Swaged victaulic one end only. Nominate overall length of hose required for quotation.