










AIP AIR HOSE COUPLINGS – QUICK CONNECT

STANDARD COUPLER - STEEL

PART No.		HOSE SIZE		PART No.		HOSE SIZE	
	20SHPFT		1/4"		20PHPFT		1/4"
	30SHPFT		3/8"		30PHPFT		3/8"
	40SHPFT		1/2"		40PHPFT		1/2"
PART No.		BSP SIZE		PART No.		BSP SIZE	
	20SMPFT		1/4"		20MPFT		1/4"
	30SMPFT		3/8"		30MPFT		3/8"
	40SMPFT		1/2"		40MPFT		1/2"
PART No.		BSP SIZE		PART No.		BSP SIZE	
	20SFPFT		1/4"		20FPFT		1/4"
	30SFPFT		3/8"		30FPFT		3/8"
	40SFPFT		1/2"		40FPFT		1/2"

ONE TOUCH COUPLER - STEEL

PART No.		HOSE SIZE	
	20SHTPFT		1/4"
	30SHTPFT		3/8"
	40SHTPFT		1/2"
PART No.		BSP SIZE	
	20SMPFT		1/4"
	30SMPFT		3/8"
	40SMPFT		1/2"
PART No.		BSP SIZE	
	20SFTPFT		1/4"
	30SFTPFT		3/8"
	40SFTPFT		1/2"

MULTI COUPLER

Complete with 1/4" male BSP couplings.

SMVPFT	SMYPFT	SMMPFT
		
POA	POA	POA

SPECIFICATION

MATERIAL	STEEL
WORKING PRESSURE	15kgf/cm ²
MAXIMUM PRESSURE	20kgf/cm ²
TEMPERATURE RANGE	-20°C TO +80°C